BT-OZ Collet Chuck

Brief introduction

Cutting Collet Chuck Tools BT 0Z Tool Holder, straight shank collet clamping tool for various sizes of cylindrical shank, high speed and high precision machining.Mechanical spindle and cutting tools and other accessories.High Precision BT shank Tool Holder ,balanced G6.3 or G2.5 For choose.

1 Name: Mill chuck BT-OZ

Material used: special alloy steel, the hardness is 45-48HRC

2.Used: special alloy steel the, hardness is 45--48HRC Material

3. Accuracy: 0.01mm Ontology

4. Description: for example BT400Z2580 Model

Stands for BT "shank BT40"

Stands for handle "type OZ25"

80 represents "length handle"

5. Types: BT400Z2580 Common

BT400Z25120

BT400Z3280

BT400Z32150

BT500Z2590

BT500Z25130

BT500Z32105

BT500Z32150

Coolant: AD, B, AD/B can be made according to cutomer requirements

ball bearing Nut

6. Dynamic balancing: G6. 3/12000rpm, G2. 5/25000rpm

OZ tool holder for heavy cutting, handle with steel ball nut design, increase the clamping force, the whole handle through hole, conducive to water and earthquake

Mode1	D2	L	D	L1	Collets
BT40-0Z25-80	3-25	80	60	30	0Z25
BT40-0Z25-120	3-25	120	60	30	0Z25
BT40-0Z32-80	6-32	80	72	33	0Z32
BT40-0Z32-150	6-32	150	72	33	0Z32
BT50-0Z25-90	3-25	90	60	30	0Z25
BT50-0Z25-130	3-25	130	60	30	0Z25

BT50-0Z32-105	6-32	105	72	33	0Z32
BT50-0Z25-150	6-32	150	72	33	0Z32

FAQ

1. What kind of characteristic of your company?

We are both manuafcturer and exporter.

2.Can you supply samples?

Yes,we can.

3.Can you produce products according to our requirement?

Yes,we can.

4. About Shipping

Port:	Shanghai/Ningbo/C	Guangzhou/Shenzhen/Hongkong
Shipping :	By Air, By Sea or B	By Express
Shipping	4-10days By Express	ifferent Area will spend different shipping
	7-15days By Air	days
	25-55days By Sea	uays
Trade Terms	FOB, CIF, EXW, C	FR, DDU

5. product warranty

One year warranty

6.What's your payment terms?

FOB,T/T,CIF.



Order No	Model No.	D2	L	D	L1	Collets
11 <mark>4</mark> 02580OZ	BT40-OZ25-80	3-25	80	60	30	0Z25
114025120OZ	BT40-0Z25-120	3-25	120	60	30	0Z25
114032800Z	BT40-0Z32-80	6-32	90	72	33	0Z32
11 <mark>4</mark> 032150OZ	BT40-OZ32-150	6-32	150	72	33	0Z32
11502590OZ	BT50-OZ25-90	3-25	90	60	30	0Z25
115025130OZ	BT50-0Z25-130	3-25	130	60	30	0Z25
115032105OZ	BT50-0Z32-105	6-32	105	72	33	0Z32
115032150OZ	BT50-OZ32-150	6-32	150	72	33	0Z32