

NT-MTB Morse Taper Adapter

Brief introduction

NT MTA Morse Taper Adapter Tool Holder, suitable for clamping type DIN228-1A with flat tail Morse tool holder. high speed and high precision machining. Mechanical spindle and cutting tools and other accessories. High Precision NT shank Tool Holder, balanced G6.3 or G2.5 For choose.

NT Tool Holders for mechanical spindle and cutting tool and other accessory tool connection. Is a simple, popular spindle shank connection standard, mainly NT30 NT40 NT50... Etc.. Mold industry, and high-speed engraving machine, used more.

Specifications

1. Material: C45
2. Size: MT1, MT2, MT3, MT4, MT5, MT6
3. Morse type. Full size as your needs.
4. Contact Surface: $\geq 85\%$
5. Standard: DIN2080
6. High quality and competitive price,
7. Delivery in time can be guaranteed since we have our own factory,
8. Strict inspection during the process of manufacturing. 1. model No.

Model	7; 24. NO. S	MS. NO. T	D (mm)	d (mm)	D1 (mm)	L (mm)
NT30-MS1	ISO30	MS1	25	12.065	31.75	113
NT30-MS2		MS2	32	17.78		118
NT30-MS3		MS3	40	23.825		138
NT30-MS4		MS4	48	31.267		212
NT40-MS1	ISO40	MS1	25	12.065	44.45	138
NT40-MS2		MS2	32	17.78		143
NT40-MS3		MS3	40	23.825		158
NT40-MS4		MS4	48	31.267		186
NT40-MS5		MS5	61	44.399		273
NT50-MS1	ISO50	MS1	25	12.065	69.85	172
NT50-MS2		MS2	32	17.78		182
NT50-MS3		MS3	40	23.825		192
NT50-MS4		MS4	48	31.267		197
NT50-MS5		MS5	61	44.399		232



Order No	Model	Capacity	D	L	C	G
333045MB1	NT30-MTB1-45	10-14	12.065	45	25	M6
333060MB2	NT30-MTB2-60	16-22	17.78	60	32	M10
333070MB3	NT30-MTB3-70	24-32	23.825	70	40	M12
334045MB1	NT40-MTB1-45	10-14	12.065	45	25	M6
334045MB2	NT40-MTB2-45	16-22	17.78	45	32	M10
334075MB3	NT40-MTB3-75	24-32	23.825	75	40	M12
334090MB4	NT40-MTB4-90	32-50	31.267	90	50	M16
335045MB1	NT50-MTB1-45	10-14	12.065	45	25	M6
335045MB2	NT50-MTB2-45	16-22	17.78	45	32	M10
335060MB3	NT50-MTB3-60	24-32	23.825	60	40	M12
335075MB4	NT50-MTB4-75	32-50	31.267	75	50	M16
3350105MB5	NT50-MTB5-105	50-75	44.399	105	65	M20
应用范围: 适用于夹持DIN228-1B型带扁尾莫氏柄刀具						